

ABS | Upright Cabinets

REFRIGERATED UPRIGHT | GLASS DOOR | INOX



GENERAL FEATURES

- 600 Lt. Refrigerated upright (GLASS DOOR)
- S/S external cabinet, thermoformed internally
- Roll-bond evaporator system with fan assisted cooling
- Automatic compressor cycle defrost
- Foaming Agent Cyclopentane (50mm per side)
- Digital Thermostat
- Removable Gasket and reversable door
- Inner LED light
- Stainless steel external handle
- Lock and main switch fitted as standard
- Adjustable shelves: 4 Pcs + 1 BOTTOM Shelf
- N.2 Adjustable feet + N.2 Rollers at the back
- Energy efficiency class: B

TECHNICAL SPECIFICATIONS

| | |
|----------------------------------|----------------|
| External Dimensions (WxDxH mm) | 775x765x1900 |
| Internal Dimensions (WxDxH mm) | 645x577x1638 |
| Noise level | 68 dB(A) |
| Consumption | 4.12 kWh/24h |
| Capacity | 600 L |
| Rated Power | 260 W |
| Net Weight | 116 Kg |
| Temperature | M2 (-1°C~+7°C) |
| Gross Weight | 128 Kg |
| Packaging dimensions (WxDxH mm) | 840x780x2060 |
| Loading quantities 20'/40'/40'HQ | 20/42/42 |

CERTIFICATION

CE RoHS



RCXG 600

M2

-1°C
+7°C

B

ENERGY CLASS

3

+25°C/60RH

30°C

GAS

R600a

50 mm

LED

DETAILS

Cabinet suitable for GN2/1 pans

Cabinet suitable for N.2 GN1/1 pans

N.12 Basket (Dim: 440x290x200 mm)

Main switch, digital thermostat and door lock fitted as standard

Digital Thermostat

External cylindric handle in stainless steel (Steel color for X Version)

PRODUCT DIMENSIONS

COOL HEAD EUROPE We make the world a cooler place

www.coolheadeurope.com