



(**) MIN 130-MAX 200 mm

| TECHNICAL DATA | | | |
|---|--------------------------|--------|--------|
| EXTERNAL DIMENSIONS | | | |
| width | 720 mm | | |
| depth | 735 mm | | |
| height | 1445/1880(open hood) mm | | |
| WEIGHT | 113 kg | | |
| VOLTAGE | 400V 3N 50Hz | | |
| POWER REQUIRED | 10490 W | | |
| WATER HARDNESS | 2-8 °F | | |
| INLET WATER PRESSURE | 200-400 kPa | | |
| CROCKERY DIMENSIONS | | | |
| plates diameter | 410 mm | | |
| trays max. dimension | GASTRONORM 1/1 (530x325) | | |
| RACK DIMENSION | 500X500 mm | | |
| RACK EQUIPMENT | 2XC40 - 1XC44 - 2X15060 | | |
| WASHING CYCLES (sec) | 1(50) | 2(100) | 3(150) |
| WATER SUPPLY 55°C | | | |
| racks/h(¹) | 72 | 36 | 24 |
| WATER SUPPLY 10°C | | | |
| racks/h(¹) | 34(×) | 36 | 24 |
| WATER CONSUMPTION / CYCLE (water pressure 200kPa) | 2.8 L | | |
| BOILER CAPACITY | 10 L | | |
| BOILER HEATING ELEMENT | 9000 W | | |
| RINSING TEMPERATURE (SET) | 85°C | | |
| TANK CAPACITY | 42 L | | |
| TANK HEATING ELEMENT | 2700 W | | |
| TANK TEMPERATURE (SET) | 55°C | | |
| PUMP POWER | 1490 W(800 L/min***) | | |
| DRAIN PUMP (optional) | - | | |
| NOISE | 63,6±0.7 dB(A) | | |

(×)START ONLY TO ACHIEVE OF 82°C ON BOILER THERMOMETER (***) MAXIMUM FLOW RATE

(¹) In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash-cycle total timing might result longer than set.