



Potato peeler PI-20 230/50/1

20 KG. / 44 POUNDS LOAD PER CYCLE.

**Stainless steel construction commercial potato peeler.
Also suitable to peel carrots and other similar products.**

High capacity and production thanks to side stirrers covered with silicon carbide abrasive (approved by NSF). Aluminium base plate lined with silicon carbide abrasive (approved by NSF). Construction in stainless steel.

- Auto-drag of waste to the drain.
- Energy optimisation thanks to engine optimisation.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- Timer 0-6min and possibility of continuous operation.

TECHNICAL SPECIFICATIONS

Hourly production: 400 Kg / 480 Kg
 Load capacity per programme: 20 Kg
 Timer (min-max): 0' - 6'
 Total Power: 550 W

Electric power supply (V) : 230 V / 50 Hz / 1 ~ / (3.5 A)
 Plug: -

External dimensions

- Width: 433 mm
- Depth: 635 mm
- Height: 735 mm

external dimensions with support

- height with support: 433 mm
- depth with support: 638 mm
- height with support: 1155 mm

Net weight: 39 Kg

Noise level (1m.): 70 dB(A)
 Background noise: 32 dB(A)

Water Intake: 80 mm

DEFAULT EQUIPMENT

OPTIONAL EQUIPMENT

- Stainless steel floor stand.
- Filter with no-foam feature.

AENOR



Empresa Registrada

ER-0437/196 UNE-EN ISO 9001



SAMMIC, S.L.
 Basarte, 1 · 20720 AZKOITIA
 www.sammic.com