



Vacuum packing machine SV-520T2 230/50-60/1

TABLETOP MODEL. 20 M³/H. 414 + 414 MM.

**Two sealing bars (414 + 414 mm.) and long-shaped chamber.
20 m³/h Busch vacuum pump.**

- Improves the durability of cooked or raw food, with no loss of weight.
- Electronic timer controlling the vacuum process and the sealing of the pack to match the preset time.
- Stainless steel body.
- Stainless steel chamber.
- Cordless sealing bars.
- Softair as standard.
- Digital keyboard.
- LED's indicate each cycle stage whilst performing.
- STOP key allows the interruption of the cycle at any stage, moving on to the next step.
- Pump drying program: improves the durability of the machine.
- Working hours counter display, which allows to know when oil must be replaced.
- NSF-International certified appliance (complying with Hygiene, Cleaning and Food Material regulations).

TECHNICAL SPECIFICATIONS

Pump capacity: 20 m³/h
Useful length of the sealing bar: 414 mm
Total Power: 750 W
Vacuum pressure (maximum): 2 mbar

230 V / 50 Hz - 60 Hz / 1 ~

Plug : EU

Internal dimensions

- Width: 560 mm
- Depth: 430 mm
- Height: 180 mm

External dimensions

- Width: 642 mm
- Depth: 557 mm
- Height: 455 mm

Net weight: 80 Kg

DEFAULT EQUIPMENT
·Insert plate set.

OPTIONAL EQUIPMENT
· Vac-Norm external vacuum kit.
· Bag cutting kit.
· Liquid insert plate set.
· Vacuum sealing bags.

